

Tabel til bestemmelse af dysestørrelser, 20-150 bar														
liter/min.														
Dysestr. \ bar	20	30	40	50	60	70	80	90	100	110	120	130	140	150
020	2	2.5	2.8	3.2	3.5	3.7	4	4.2	4.5	4.7	4.8	5	5.3	5.4
025	2.5	3.1	3.5	4	4.3	4.7	5	5.3	5.6	5.9	6.1	6.4	6.6	6.9
030	3.1	3.7	4.3	4.8	5.3	5.7	6.1	6.3	6.8	7.1	7.4	7.7	8	8.3
035	3.8	4.2	4.9	5.5	6	6.5	7	7.4	7.8	8.2	8.6	8.9	9.2	9.5
040	4.2	5.2	5.9	6.6	7.3	7.8	8.4	8.9	9.4	9.8	10.3	10.7	11.1	11.5
045	4.5	5.5	6.4	7.1	7.8	8.4	9	9.6	10.2	10.5	10.9	11.4	11.8	12.2
050	5	6.2	7.1	8	8.7	9.4	10	10.7	11.3	11.8	12.4	12.9	13.4	13.8
055	5.6	6.8	7.8	8.7	9.6	10.3	11.1	11.8	12.4	13	13.6	14.1	14.7	15.2
060	6	7.4	8.6	9.6	10.4	11.3	12.1	12.8	13.6	14.3	14.9	15.5	16	16.7
065	6.6	8	9.3	10.4	11.3	12.3	13.2	14	14.7	15.4	16.1	16.8	17.4	18
070	7.1	8.6	10	11.2	12.2	13.2	14.1	15	15.8	16.6	17.3	18	18.7	19.3
075	7.6	9.3	10.7	12	13.1	14.2	15.2	16.1	16.9	17.7	18.5	19.3	20	20.7
080	8	9.8	11.3	12.7	14	15.1	16.1	17.1	18	18.9	19.7	20.5	21.3	22
085	8.5	10.4	12.1	13.5	14.8	16	17.1	18.1	19.1	20	20.9	21.8	22.6	23.4
090	9.1	11.1	12.8	14.3	15.7	17	18	19.2	20.2	21.2	22.1	23	23.9	24.7
10	10	12.3	14.2	16	17.4	18.9	20.1	21.4	22.5	23.6	24.6	25.6	26.6	27.6
11	10.9	13.4	15.5	17.3	19	20.5	22	23.3	24.5	25.7	26.9	28	29.1	30.1
12	11.9	14.6	16.9	18.9	20.8	22.4	24	25.4	26.8	28.1	29.4	30.6	31.7	32.8
13	13.1	15.9	18.3	20.5	22.5	24.3	26	27.5	29	30.4	31.8	33.1	34.4	35.6
14	13.9	17.1	19.7	22.1	24.2	26.1	28	29.6	31.3	32.8	34.2	35.6	37	38.3
15	14	18.5	21.3	23.9	26.1	28.3	30.2	32.1	33.8	35.3	36.9	38.4	39.9	41.3
20	20.1	24.7	28.5	31.9	34.9	37.8	40.3	42.7	45.1	47.2	49.3	51.3	53.2	55.1

Tabel til bestemmelse af dysestørrelser, 160-500 bar										
liter/min.										
Dysestr. \ bar	160	175	200	225	250	300	350	400	450	500
020	5.6	5.9	6.3	6.7	7	7.9	8.5	9	9.6	10.2
025	7.1	7.5	8	8.5	9	9.7	10.5	11.2	12	12.6
030	8.6	9	9.6	10.2	10.7	11.9	12.8	13.6	14.5	15.2
035	9.8	10.3	11	11.7	12.3	13.5	14.6	15.6	16.5	17.3
040	11.9	12.4	13.3	14.1	14.8	15.8	17	18.2	19.3	20.2
045	12.6	13.2	14.1	15	15.8	17.9	19.3	20.7	21.8	22.9
050	14.3	14.9	16	16.9	17.9	19.8	21.3	22.9	24.2	25.6
055	15.7	16.4	17.5	18.6	19.6	21.7	23.5	25.1	26.6	28.2
060	17.2	18	19.2	20.4	21.5	23.7	25.7	27.5	29.2	30.7
065	18.6	19.4	20.8	22	23.2	25.7	27.8	29.7	31.5	33.2
070	20	20.9	22.3	23.7	25	27.8	29.9	32.1	34.1	36
075	21.4	22.4	23.9	25.3	26.7	29.6	32	34.2	36.3	38.2
080	22.8	23.8	25.2	27	28.5	31.5	34.1	36.3	38.5	40.8
085	24.1	25.3	27	28.6	30.2	33.5	36.1	38.7	41.1	43.5
090	25.5	26.7	28.6	30.3	31.9	36.4	39.3	41.8	44.4	47.1
10	28.5	29.8	31.8	33.7	35.6	39.7	43.1	46.2	49	51.5
11	31.1	32.5	34.7	36.8	38.8	43.2	46.7	50.1	53.1	55.9
12	33.9	35.4	37.9	40.2	42.4	46.8	50.4	54.1	57.3	60.4
13	36.7	38.4	41.1	43.6	45.9	51.9	56.2	60.2	63.6	67.1
14	39.5	41.4	44.3	46.9	49.4	55.4	60	63.9	67.9	71.6
15	42.6	44.6	47.7	50.6	53.3	58.8	63.5	68.1	72.1	76.1
20	56.9	59.5	63.6	67.5	71.1	79.6	86.2	92.1	97.8	103.3

Sådan finder du dysestørrelsen i skemaet.

1) Se på maskinen, der står typisk dysestørrelse eller maks. tryk/vandmængde.

2) Står der f.eks. 160 bar / 20 liter, så viser tabellen, at dysestørrelsen skal være 070.

Tabel til bestemmelse af dysestørrelser, 160-500 bar										
liter/min.										
Dysestr. \ bar	160	175	200	225	250	300	350	400	450	500
020	5.6	5.9	6.3	6.7	7	7.9	8.5	9	9.6	10.2
025	7.1	7.5	8	8.5	9	9.7	10.5	11.2	12	12.6
030	8.6	9	9.6	10.2	10.7	11.9	12.8	13.6	14.5	15.2
035	9.8	10.3	11	11.7	12.3	13.5	14.6	15.6	16.5	17.3
040	11.9	12.4	13.3	14.1	14.8	15.8	17	18.2	19.3	20.2
045	12.6	13.2	14.1	15	15.8	17.9	19.3	20.7	21.8	22.9
050	14.3	14.9	16	16.9	17.9	19.8	21.3	22.9	24.2	25.6
055	15.7	16.4	17.5	18.6	19.6	21.7	23.5	25.1	26.6	28.2
060	17.2	18	19.2	20.4	21.5	23.7	25.7	27.5	29.2	30.7
065	18.6	19.4	20.8	22	23.2	25.7	27.8	29.7	31.5	33.2
070	20	20.9	22.3	23.7	25	27.8	29.9	32.1	34.1	36
075	21.4	22.4	23.9	25.3	26.7	29.6	32	34.2	36.3	38.2
080	22.8	23.8	25.2	27	28.5	31.5	34.1	36.3	38.5	40.8
085	24.1	25.3	27	28.6	30.2	33.5	36.1	38.7	41.1	43.5
090	25.5	26.7	28.6	30.3	31.9	36.4	39.3	41.8	44.4	47.1
10	28.5	29.8	31.8	33.7	35.6	39.7	43.1	46.2	49	51.5
11	31.1	32.5	34.7	36.8	38.8	43.2	46.7	50.1	53.1	55.9

Tabel til bestemmelse af dysestørrelser, 160-500 bar										
liter/min.										
Dysestr. \ bar	160	175	200	225	250	300	350	400	450	500
020	5.6	5.9	6.3	6.7	7	7.9	8.5	9	9.6	10.2
025	7.1	7.5	8	8.5	9	9.7	10.5	11.2	12	12.6
030	8.6	9	9.6	10.2	10.7	11.9	12.8	13.6	14.5	15.2
035	9.8	10.3	11	11.7	12.3	13.5	14.6	15.6	16.5	17.3
040	11.9	12.4	13.3	14.1	14.8	15.8	17	18.2	19.3	20.2
045	12.6	13.2	14.1	15	15.8	17.9	19.3	20.7	21.8	22.9
050	14.3	14.9	16	16.9	17.9	19.8	21.3	22.9	24.2	25.6
055	15.7	16.4	17.5	18.6	19.6	21.7	23.5	25.1	26.6	28.2
060	17.2	18	19.2	20.4	21.5	23.7	25.7	27.5	29.2	30.7
065	18.6	19.4	20.8	22	23.2	25.7	27.8	29.7	31.5	33.2
070	20	20.9	22.3	23.7	25	27.8	29.9	32.1	34.1	36
075	21.4	22.4	23.9	25.3	26.7	29.6	32	34.2	36.3	38.2
080	22.8	23.8	25.2	27	28.5	31.5	34.1	36.3	38.5	40.8
085	24.1	25.3	27	28.6	30.2	33.5	36.1	38.7	41.1	43.5
090	25.5	26.7	28.6	30.3	31.9	36.4	39.3	41.8	44.4	47.1
10	28.5	29.8	31.8	33.7	35.6	39.7	43.1	46.2	49	51.5
11	31.1	32.5	34.7	36.8	38.8	43.2	46.7	50.1	53.1	55.9